

# Specifications

# Apple Color OneScanner 1200/30





Specifications

## Characteristics (Flatbed)

Scanner Type Flatbed, single-pass, 30-bit scanning

Scanner Resolution 600 x 1200 dpi 4800 x 4800 dpi interpolated

Maximum Document Size 8.5 x 11.7 in. (21.6 x 29.2 cm)
8.5 x 14 in. (21.6 x 35.6 cm) with optional Automatic Document Feeder (ADF)

Speed

6 seconds (full-page preview) 20 seconds (US letter size) Monochrome: 10 seconds (US letter size)



	0	
-	_	

Specifications

#### Interface SCSI-2

Options

Automatic Document Feeder (ADF) Transparent Media Adapter (TMA)

System Requirements 13-inch display or larger
System software version 7.5 or later
At least 8 MB of RAM (need to increase memory additional 2 MB when using OneScanner Dispatcher with Kai's Power Tools or Convolver; 12 MB required to use OneScanner Dispatcher and Xerox TextBridge OCR software simultaneously)





### Electrical

Line Voltage 100/120/200/220/240 VAC ± 10%

Frequency 50–60 Hz

Power Consumption 35 W maximum





# Physical

Height: 3.1 in (79 mm)
Width: 11.3 in (287 mm)
Depth: 16.3 in (414 mm)

Weight

12.1 lb (5.5 kg)





### Environmental

Operating	With the ADF: 50 to 90.5°F (10 to 32.5°C)
Temperature	Without the ADF: 41 to 95°F (5 to 35°C)
<b>Relative Humidity</b>	With the ADF: 20 to 80% noncondensing Without the ADF: 15 to 85% noncondensing

