



# Tech Info Library

## A/UX: Setting sash Variable From the Menu

Article Created: 29 June 1988

### Article Change History

08/31/92 - REVIEWED

- For technical accuracy.

### TOPIC -----

Setting "sash" Variable From the Menu

### DISCUSSION -----

If the root directory controller number is changed in the Preferences menu, the "sash" variable is not adjusted to the new value. To pick up the change, you have quit from the "sash" and rerun it.

Normally, when "sash" is first invoked, it performs a "chroot" command to whatever "sash" variable "ROOT" was set to in a previous session. If the root directory controller number in the menu is changed, the "sash" variable "ROOT" changes to that number -- but it is not "export"ed.

To launch A/UX from a different drive, choose either of the following methods:

- Issue the "launch (x, y, z)/unix" command.

- or -

- 1) Issue the "chroot (x, y, z)" command (where x is the SCSI ID, y is SCSI subdrive ID, and z is the slice number in the drive).
- 2) Then issue the "launch" command. (Selecting a different controller number from the menu or setting the variable "ROOT" immediately does not affect the change on the root directory.)

Copyright 1988 Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 3077