



Tech Info Library

A/UX 2.0: How to Escape from a Hung Login Under X Windows

Article Created: 19 June 1990

Article Change History

08/31/92 - REVIEWED

- For technical accuracy.

TOPIC -----

I created an interesting problem for myself. I was preparing a Macintosh IIIfx with X Window and mistyped a line into the PATH variable. When I tried to log in, I hung. I was finally able to break out of the login process, but it was time-consuming and not very intuitive. The typo was `/usr/lib/X11`, instead of `/usr/bin/X11`. Obviously, this didn't let the process look in the right place for the software, so it wouldn't boot properly.

Do you have any suggestions?

DISCUSSION -----

As we have tested the above X11 session scenario (login as "Guest" without the `/usr/bin/X11` in the search PATH) we won't get into the "hung" situation. It is true that the screen displays, "Starting session for Guest...", if no one presses the Return key.

At that "hung" point, however, if you only press Return, the default X11 session will come up. The default X11 session includes a "Console" window, two "xterm" windows, and three X client applications (xlogo, xload, and xclock). If you have pressed any printable key then Return, it will bring you back to the Login dialog box.

As we examine the `/usr/bin/X11/X11` script, the above behavior becomes clear, because the X11 script does check if `/usr/bin/X11` is in your search path, then asks you if it should be appended to your search path. This is why the "Starting session for Guest..." message was waiting for your reply.

Note that the "x11debug.log" file will be created under the user's home directory, if any error is encountered. Check with that file for an explanation.

Copyright 1990 Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 5894