



Tech Info Library

ABS Tech Note: SNA•ps04 Bullets in Admin (5/92)

Article Created: 29 May 1992

TOPIC -----

This technical note explains the meaning of the bullets that show up in the SNA•ps Admin status display.

DISCUSSION -----

Introduction

The small black circles that appear in the gateway status display in SNA•ps Admin are intended to give a general indication of the state of the particular resource in the gateway. Detailed state information can be found by opening the resource. The exact meaning of the status indicators is given here.

For all resources except for 3270 LUs:

- A bullet (" • ") displayed indicates that the resource is in the active state.
- A small open circle (" ° ") displayed indicates that the resource is always activated.
- No symbol displayed indicates that the resource is not in the active state.

For 3270 LUs:

- A bullet displayed indicates that the LU is in use by an application program such as the SNA•ps 3270 terminal emulator.
- A question mark (" ? ") displayed indicates that this is an LU with an ID of zero. This will occur when a coax gateway is not in contact with the IBM 3174 controller, or if the 3174 controller has not been configured properly.
- No symbol displayed indicates that the LU is not in use by any client application. If it is a coax line, then the gateway is in contact with

the 3174 controller, and the LU has been configured at the controller.

For APPC Modes:

- A bullet displayed indicates that the session limits for the mode have been initialized and are greater than 0.
- No symbol displayed indicates that the mode has not yet had its limits initialized.

Copyright 1993, Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 11690