

# Tech Info Library

# Power Macintosh 5500/225: Technical Specifications (2/97)

Article Created: 19 January 1997 Article Reviewed/Updated: 13 February 1997 TOPIC -----This article contains the technical specifications for the Power Macintosh 5500/225 computer. DISCUSSION -----Microprocessor ========== \* PowerPC 603ev processor running at 225 MHz \* Integrated floating-point unit \* 50-MHz, 64-bit bus \* 32K internal cache \* 256K level 2 cache Memory ===== \* Two DIMM expansion slots, no RAM on logic board \* Includes 32 MB of memory \* Can be expanded to 128 MB \* Uses 64-bit-wide, 168-pin, EDO DIMMs (1K or 2K refresh) Disk drives -----\* Internal 2.0 GB IDE hard disk drive \* Internal Apple SuperDrive floppy disk drive - Uses high-density, 1.4MB floppy disks - Reads, writes, and formats Macintosh, Windows, MS-DOS, OS/2, and ProDOS disks \* Internal AppleCD 12x drive Display ====== Built-in display \_\_\_\_\_ \* 15-in. RGB color display (12.8-in. diagonal viewable image size) \* 0.28-mm dot pitch \* Noninterlaced, flat, square cathode-ray tube (CRT)

- \* User-adjustable resolutions from 640 by 480 pixels to 832 by 624 pixels
- \* Resolution can be changed without restarting the computer
- \* Refresh rate up to 75 Hz
- \* Built-in base tilts from -5 to +15 degrees, swivels a full 360 degrees
- \* Meets SWEDAC MPR2 international guidelines for magnetic-field emissions

#### Graphics support

\_\_\_\_\_\_

- \* 2 MB synchronous graphics RAM (SGRAM) frame buffer on the logic board.
- \* Video display modes supported on built-in monitor port: 640 by 480, 800 by 600, and 832 by 624 at 32 bits per pixel; 1024 by 768 and 1152 by 870 at 16 bits per pixel; 1280 by 1024 at 8 bits per pixel
- \* Built-in 2D and 3D hardware graphics acceleration.

#### Sound

=====

- \* Stereo 16-bit sound
- \* Apple sound enhancements, including SRS 3D surround sound
- \* Built-in stereo speakers
- \* Built-in microphone
- \* Sound-output port
- \* Sound-input port
- \* Front headphone jack and volume control

#### Expansion interfaces

- \* PCI expansion slot for industry-standard 6.88-in., 15-watt expansion cards
- \* Apple Desktop Bus port for mouse, keyboard, and other devices (multiple devices can be connected

to each other from one port)

- \* RS-232/RS-422 serial port for an AppleTalk network connection, other networking connections, communications equipment (including GeoPort-compatible devices), or a printer
- \* SCSI interface port for as many as six external SCSI devices, such as disk drives and/or CD-ROM drives
- \* Communications slot (used by the built-in Ethernet connector)
- \* TV/FM radio expansion bay
- \* Video-output port for connection to an external monitor for video mirroring (also supports connection to an NTSC or PAL video-out interface box, such as the Apple Presentation System)
- \* Video-input connector (Apple Video System) for receiving video input from a VCR, video camera, or other video equipment; supports both composite and S-video input

# Disability access

==========

- \* CloseView software magnifies screen image up to 16 times
- \* Easy Access software permits combination keys to be pressed sequentially and enables cursor control from the numeric keypad instead of the mouse
- \* "Visual beep" replaces audible system alerts

Electrical requirements and compliance

- \* Line voltage: 110 to 240 V AC, RMS, single phase, nominal
- \* Frequency: 50 to 60 Hz
- \* Power: 220 W maximum (continuous)
- \* Includes low-power sleep mode
- \* U.S. EPA Energy Star compliant

### Size and weight

=========

\* Height: 17.5 in. (44.5 cm)

\* Width: 15.1 in. (38.3 cm)

\* Depth: 16 in. (40.6 cm)

\* Weight: 47 lb. (21 kg)

# Operating environment

- \* Operating temperature: 50 to 104 degrees F (10 to 40 degrees C)
- \* Storage temperature: -40 to 116 degrees F (-40 to 47 degrees C)
- \* Relative humidity: 5% to 95%, noncondensing
- \* Maximum altitude: 10,000 ft. (3,048 m)

## Configurations

==========

Power Macintosh 5500/225

\_\_\_\_\_\_

Order No. M5761LL/A

Computer with 225-MHz PowerPC 603ev processor, 32 MB of RAM, 256K level 2 cache, built-in Ethernet, 2.0 GB hard disk drive, 12x-speed CD-ROM drive, 1.4 MB floppy disk drive, and Apple Video System.

Article Change History:

13 Feb 1996 - Changed distribution status.

Copyright 1997, Apple Computer, Inc.

Keywords: kppc, specsht

\_\_\_\_\_\_

This information is from the Apple Technical Information Library.

ArticleID: TECHINFO-0020816

19970214 11:37:46.00

Tech Info Library Article Number: 20816