

## Power Macintosh 6500/225 & 6500/250: Specifications (2/97)

Article Created: 19 January 1997 Article Reviewed/Updated: 13 February 1997 TOPIC ------This article contains the technical specifications for Power Macintosh 6500/225 and 6500/250 series computers. DISCUSSION ------Microprocessor \_\_\_\_\_ \* PowerPC 603ev processor running at 225 MHz (Power Macintosh 6500/225) \* PowerPC 603ev processor running at 250 MHz (Power Macintosh 6500/250) \* Integrated floating-point unit \* 50-MHz, 64-bit bus \* 32K internal cache \* 256K level 2 cache Memory ===== \* Two DIMM expansion slots, no RAM on logic board \* Includes 32 MB of memory \* Can be expanded to 128 MB \* Uses 64-bit-wide, 168-pin, EDO DIMMs (1K or 2K refresh) Disk drives ============ \* Internal 2.0 GB IDE hard disk drive (Power Macintosh 6500/225) \* Internal 3.0 GB IDE hard disk drive (Power Macintosh 6500/250) \* Internal Apple SuperDrive floppy disk drive - Uses high-density, 1.4MB floppy disks - Reads, writes, and formats Macintosh, Windows, MS-DOS, OS/2, and ProDOS disks \* Internal AppleCD 12x drive \* Internal Iomega Zip Drive (each cartridge can hold 100 MB) Sound ===== \* Stereo 16-bit sound \* SRS surround-sound enhancement

\* Subwoofer speaker

\* Sound-input port (for an Apple PlainTalk microphone, other microphone, or standard mini-plug audio cable)

\* Sound-output port

\* Front headphone jack and volume control

## Interfaces

\* SCSI interface port for connecting as many as five external SCSI devices, such as disk drives, CD-ROM drives, and scanners (multiple devices can be connected to each other from one port) \* Pre-cabled SCSI expansion bay for additional 5.25-inch internal SCSI device \* Apple Desktop Bus port for mouse, keyboard, and other devices (multiple devices can be connected to each other from one port) \* Two serial ports (RS-232/RS-422) for an AppleTalk network connection, other network connections, communications equipment (including GeoPort compatible devices), or a printer \* Video-output port \* Two PCI expansion slots (require PCI cards that come with a Macintosh driver and are PCI 2.0-compliant; NuBus cards cannot be used in these slots) \* Communications (Comm II) slot for a 28.8-Kbit/s modem (used by included Ethernet Card)) \* Video input slot for Apple Video System (supports NTSC, PAL, and SECAM video formats) (Apple Video System included with Power Macintosh 6500/250) \* Expansion bay for optional Apple TV/FM Radio System \* Infrared receiver for remote control (provided with Apple TV/FM Radio System) Graphics support \_\_\_\_\_ \* 2 MB synchronous graphics RAM (SGRAM) frame buffer on the logic board. \* Video display modes supported on built-in monitor port: 640 by 480, 800 by 600, and 832 by 624 at 32 bits per pixel; 1024 by 768 and 1152 by 870 at 16 bits per pixel; 1280 by 1024 at 8 bits per pixel \* Built-in 2D and 3D hardware graphics acceleration. Electrical requirements and compliance \_\_\_\_\_ \* Line voltage: 90-130 volts (V) or 180-264 V alternating current (AC), RMS single phase. The computer's voltage needs to be configured manually. \* Frequency: 47 to 63 Hz \* Power: 140 watts (W) maximum continuous input power Size and weight \_\_\_\_\_ \* Height: 16 in. (40.6 cm) \* Width: 7.8 in. (19.8 cm) \* Depth: 16.9 in. (42.8 cm) \* Weight: 44.5 lb. (20.18 kg) Operating environment \_\_\_\_\_ \* Operating temperature: 50 to 97 degrees F (10 to 35 degrees C) \* Storage temperature: -40 to 116.6 degrees F (-40 to 47 degrees C)

\* Relative humidity: 5% to 95%, noncondensing \* Maximum altitude: 10,000 ft. (3,048 m) Disability access \_\_\_\_\_ \* CloseView software magnifies screen image up to 16 times \* Easy Access software permits combination keys to be pressed sequentially and enables cursor control from the numeric keypad instead of the mouse \* Visual beep replaces audible system alertss Configurations \_\_\_\_\_ Power Macintosh 6500/225 \_\_\_\_\_ Order No. M5606LL/A Computer with 225-MHz PowerPC 603ev processor, 32 MB of RAM, 256K level 2 cache, built-in Ethernet, 2.0 GB hard disk drive, Zip drive, 12x-speed CD-ROM drive, and 1.4 MB floppy disk drive. Power Macintosh 6500/250 \_\_\_\_\_ Order No. M5607LL/A Computer with 250-MHz PowerPC 603ev processor, 32 MB of RAM, 256K level 2 cache, built-in Ethernet, 3.0 GB hard disk drive, Zip drive, 12x-speed CD-ROM drive, 1.4 MB floppy disk drive, and Apple Video System. Article Change History: 13 Feb 1997 - Changed distribution status. Copyright 1997, Apple Computer, Inc. Keywords: kppc, specsht \_\_\_\_\_ This information is from the Apple Technical Information Library. ArticleID: TECHINFO-0020815 19970214 11:37:46.00 Tech Info Library Article Number: 20815