



Tech Info Library

Power Macintosh 7500 Series: Technical Specifications (9/96)

Article Created: 6 July 1995

Article Reviewed/Updated: 17 September 1996

TOPIC -----

This article contains the technical specifications for the Power Macintosh 7500 series of computers.

DISCUSSION -----

Upgradable Microprocessor

- PowerPC 601 microprocessor running at 100 MHz, upgradable to PowerPC 604 microprocessor
- Integrated floating-point unit and 32K cache
- High-speed system bus (up to 50 MHz)

Memory

- RAM: 16 MB of RAM, expandable to 512 MB via 8 DIMM sockets
(Note: There is no RAM soldered to the logic board. The DIMM sizes installed at the factory will vary according to availability; there will be either two 8 MB DIMMs or one 16 MB DIMM. If you are installing more RAM, the DIMMs should be 64-bit-wide, 168-pin fast-paged mode, with 70-ns RAM access times or faster.)
- Optional Level 2 (L2) Cache: L2 Cache Slot for optional 256K, 512K, or 1MB L2 cache on a 160-pin DIMM. (Theoretical Support for up to 4 MB of L2 cache.)
- VRAM: 2 MB of VRAM, expandable to 4 MB.
DIMMs must be 32-bit-wide, 112-pin fast-paged mode with 70ns RAM access time or faster. Do not use the 256 K or 512 K VRAM SIMMs used in older Macintosh computers.
- 4 MB of ROM

Disk Drives

- Internal 500 MB or 1 GB Fast SCSI hard disk
- Internal Apple SuperDrive floppy disk drive
 - Accepts high-density 1.4 MB disks and 800K disks
 - Reads, writes, and formats Macintosh, Windows, MS-DOS, OS/2, and ProDOS disks
- Internal AppleCD 600i quadruple-speed CD-ROM drive
- Expansion bay for additional 3.5-inch hard disk

Interfaces

- Three PCI expansion slots compatible with PCI 2.0-compliant cards (Note: These slots are not NuBus-compatible)
- Two high-speed DMA serial (RS-232/RS-422) ports compatible with LocalTalk and GeoPort cables
- 10Base-T and AAUI-15 Ethernet connectors
- Internal Fast SCSI bus (up to 10 MB/s)
- External SCSI bus (up to 5 MB/s)
- Apple Desktop Bus (ADB) expansion port
- RCA phono jacks for line-level stereo audio input and output
- Mini jacks for stereo audio input and output
- All sound ports support 16-bit audio and up to 44.1-kHz sampling rate
- DB-15 connector for monitor
- Composite connectors (RCA phono jacks) for composite video input
- S-video input connector
- Internal digital audio/video (DAV) connector for video compression/decompression cards 24-bit video input
- Real-time video playthrough of up to 640 by 480 pixels with NTSC and 768 by 576 pixels with PAL and SECAM
- Up to 320- by 240-pixel capture at 15 frames per second with NTSC
- Maximum capture size of 640 by 480 pixels with NTSC

Audio System

- Custom sound circuitry, including stereo generator (digital-to-analog converter, or DAC)—capable of driving stereo miniplug headphones or audio equipment—and stereo sampling hardware (analog-to-digital converter, or ADC) for recording stereo sound
- 16-bit stereo input and output
- Sample rates of 44.1 and 22.05 kilohertz (kHz)
- Sound input connector line level: 2.8 volts peak-to-peak (Vpp) nominal, into 3.0-kilohm (k Ω) impedance (minimum)
- RCA-type input connector line level: 2.4 Vpp nominal, into 13.5-k Ω impedance (minimum)
- Sound output connector line level: 2.7 Vpp nominal, into 32-k Ω impedance
- RCA-type output connector level: 2.9 Vpp nominal into 2-k Ω impedance (minimum)
- Sound input signal-to-noise ratio (SNR): >83 decibels (dB) A-weighted with no audible discrete tones
- RCA-type input SNR: >77 dB A-weighted with no audible discrete tones
- Sound output SNR: >84 dB A-weighted with no audible discrete tones
- RCA-type output SNR: >84 dB A-weighted with no audible discrete tones
- Bandwidth: 10 Hz to 18 kHz (+0.1 dB, -3.0 dB) at 44.1-kHz sample rate
- RCA-type input total harmonic distortion plus noise (THD + N): less than 0.018 percent A-weighted; measured 10 Hz to 30 kHz with a 2.4-Vpp sine wave input

Graphics Support

- 2 MB of VRAM, expandable to 4 MB
- Fast 64-bit data path to VRAM

- Support for display resolutions of up to 1,280 by 1,024 pixels
- 24-bit color of up to 1,152- by 870-pixel resolution
- Refresh rate of up to 75 Hz

GeoPort Telephony*

-
- 14.4-Kbit/s modem support
 - V.17 fax support
 - GeoPort Fax and GeoPort Telephony software included
 - Speakerphone and answering-machine capability
- * Requires GeoPort Telecom Adapter

Clock/Calendar

-
- Custom integrated circuit with long-life battery

Keyboard And Mouse

-
- Supports ADB keyboards with numeric keypads
 - Comes with an ADB Mouse II

Electrical Requirements And Compliance

-
- Line voltage: 100 to 240 V AC, RMS single phase
 - Frequency: 50 to 60 Hz, single phase
 - Power: 150 W maximum, not including display

ADB Power Requirements

-
- Maximum current draw for all devices: 500 mA
(a maximum of three ADB devices is recommended)
 - Mouse draws 10 mA
 - Keyboard draws 25 to 80 mA (varies with keyboard used)

Size And Weight

-
- Height: 6.15 in. (15.6 cm)
 - Width: 14.37 in. (36.5 cm)
 - Depth: 16.93 in. (43.0 cm)
 - Weight: 22 lb. (9.97 kg)

Operating Environment

-
- Operating temperature: 50 degrees to 104 degrees F
(10 degrees to 40 degrees C)
 - Storage temperature: -40 degrees to 116 degrees F
(-40 degrees to 47 degrees C)
 - Relative humidity: 5% to 95% noncondensing
 - Maximum altitude: 10,000 ft. (3,048 m)

Article Change History:

17 Sep 1996 - Updated information.

02 Jan 1996 - Clarified VRAM information.
18 Sep 1995 - Corrected minor typo.

Copyright 1995-96, Apple Computer, Inc.

Keywords: kppc,kpci,specsht

=====

This information is from the Apple Technical Information Library.

19960918 07:30:18.00

Tech Info Library Article Number: 18080