



Tech Info Library

Power Macintosh 9500/180MP and 9500/200: Specifications (9/96)

Article Created: 25 July 1996

Article Reviewed/Updated: 11 August 1996

TOPIC -----

This article contains the technical specifications for the Power Macintosh 9500/180MP and 9500/200.

DISCUSSION -----

Upgradable microprocessor

=====

- * One 200-MHz PowerPC 604e processor or two 180-MHz PowerPC 604e processors
- * Integrated floating-point unit and 64K cache
- * High-speed system bus (up to 50 MHz)
- * Upgradability (up to 250 MHz)

Memory

=====

- * 16 MB or 32 MB of RAM, expandable to 768 MB via 12 DIMM sockets
- * 4 MB of ROM
- * 512K level 2 cache

Disk drives

=====

- * Internal 2GB Fast SCSI hard disk
- * Internal Apple SuperDrive floppy disk drive
 - Accepts high-density 1.4 MB disks and 800K disks
 - Reads, writes, and formats Macintosh, Windows, MS-DOS, OS/2, and ProDOS disks
- * Internal 8x-speed CD-ROM drive
- * Two expansion bays for additional 3.5-inch hard disks

Interfaces

=====

- * Six PCI expansion slots compatible with PCI 2.0-compliant cards
- * Two high-speed DMA serial (RS-232/RS-422) ports compatible with LocalTalk and GeoPort cables
- * 10BASE-T and AAUI-15 Ethernet connectors; optional PC Compatibility Cards provide multinode support for simultaneous network connections
- * Internal Fast SCSI bus (up to 10MB/s)
- * External SCSI bus (up to 5MB/s)

- * Apple Desktop Bus (ADB) expansion port
- * Mini jacks for stereo audio input and output
- * 16-bit stereo sound input and output ports
- * DB-15 connector for monitor (on accelerated graphics card)

Graphics support

=====

(configured through accelerated graphics card)

- * 2 MB of VRAM, expandable to 4 MB
- * Support for display resolutions of up to 1,280 by 1,024 pixels
- * 24-bit color up to 1,152- by 870-pixel resolution
- * Refresh rate of up to 75 Hz

GeoPort telephony

=====

- * 14.4-Kbit/s modem support
- * V.17 fax support
- * GeoPort Fax and GeoPort Telephony software included
- * Speakerphone and answering-machine capability

Clock/calendar

=====

- * Custom integrated circuit with long-life battery

Keyboard and mouse

=====

- * Supports ADB keyboards with numeric keypads
- * Comes with an ADB Mouse II

Electrical requirements

=====

- * Line voltage: 100 to 125 and 200 to 240 V AC, RMS single phase, automatically configured
- * Frequency: 50 to 60 Hz, single phase
- * Power: 225 W maximum, not including display

ADB power requirements

=====

- * Maximum current draw for all ADB devices: 500 mA (a maximum of three ADB devices is recommended)
- * Mouse draws 10 mA
- * Keyboard draws 25 to 80 mA (varies with keyboard used)

Size and weight

=====

- * Height: 16.9 in. (43.0 cm)
- * Width: 7.7 in. (19.6 cm)
- * Depth: 15.75 in. (40.0 cm)
- * Weight: 28 lb. (12.7 kg)

Environmental requirements

=====

- * Operating temperature: 50 to 104 degrees F (10 to 40 degrees C)

- * Storage temperature: -40 to 116 degrees F (-40 to 47 degrees C)
- * Relative humidity: 5% to 95% noncondensing
- * Maximum altitude: 10,000 ft. (3,048 m)

Article Change History:

11 Sep 1996 - Updated information.

02 Aug 1996 - Changed distribution status.

Copyright 1996, Apple Computer, Inc.

Keywords: kppc,specsht

=====

This information is from the Apple Technical Information Library.

19960912 07:58:46.00

Tech Info Library Article Number: 20209