

Tech Info Library

System Software:Installation On a One-Floppy-Drive System (2/95)

| Article Created: 25 May 1989 Article Reviewed/Updated: 22 February 1995 |
|--|
| TOPIC |
| This article explains a workaround for system software installation on a one-floppy-drive system. |
| DISCUSSION |
| If your Macintosh has only one floppy disk drive and no hard disk drive (for example: a Macintosh II, Macintosh IIx, or Macintosh SE/30 with no hard disk), you can still install system software 6.0.3 onto a bootable floppy disk. |
| Such a System Software upgrade, even on a Macintosh IIx with an Apple SuperDrive (formerly Apple FDHD), takes 402 disk insertions (or disk swaps). |
| Rather than numerous disk insertions/swaps, a simpler procedure may be to use a RAM-disk program. On a system with 2 or more megabytes (MB) of RAM, you can create a RAM disk of 800K to 1500K, and then copy the Installer and associated files to it. The Finder on the RAM-disk could be Option-clicked to make it become the start-up disk. After restarting with the RAM disk as your startup disk, you can run the installation as though a two-floppy system were being used. |
| Article Change History: 22 Feb 1995 - Reviewed for technical accuracy and added the commonly used term "disk swap" to enhance searching capabilities. 22 Aug 1991 - Reviewed for technical accuracy. |
| Support Information Services Copyright 1991-95, Apple Computer, Inc. |
| Keywords: supt,ksts |
| |
| This information is from the Apple Technical Information Library. |

19960215 11:05:19.00

Tech Info Library Article Number: 3803