



Tech Info Library

AppleVision 1710 Display: Technical Specifications (1/96)

Article Created: 31 January 1996

TOPIC -----

This article contains the technical specifications of the AppleVision 1710 Display.

DISCUSSION -----

Picture Tube

- 17-in. (diagonal) Trinitron CRT
- 16.1 in. (diagonal viewable image size)
- 0.26-mm stripe pitch (0.25-mm grille pitch)

Resolution/Screen Refresh Rate

Macintosh computers:

- 640 by 480 pixels at 67 Hz
- 832 by 624 pixels at 75 Hz
- 1,024 by 768 pixels at 75 Hz
- 1,152 by 870 pixels at 75 Hz
- 1,280 by 1,024 pixels at 75 Hz

PC-compatible systems:

- 640 by 480 pixels at 60 Hz to 75 Hz
- 800 by 600 pixels at 60 Hz to 75 Hz
- 1,024 by 768 pixels at 60 Hz to 75 Hz
- 1,280 by 1,024 pixels at 60 Hz to 75 Hz

Scanning Rates

- 30 kHz to 80 kHz (horizontal)
- 40 Hz to 120 Hz (vertical)

Apple DigitalColor Technology Features

- Self-calibration against factory measurements
- Adjustment for ambient lighting
- Adjustment for CRT phosphor aging

Screen Treatment

- Antistatic, antiglare coating

Digital Controls

- Brightness
- Contrast
- Horizontal size and centering
- Vertical size and centering
- Convergence
- Rotation
- Pincushion
- Completely variable white-point selection: 4,100 deg. K to 9,300 deg. K
- Power switch

Connector

- 15-pin DSub connector for Macintosh systems
- 15-pin DSub mini-adapter for PCs

Degauss Circuitry

- Automatic at power up

Electrical Requirements

- Line voltage: 90 to 264 V AC
- Frequency: 47 to 63 Hz, single phase
- Power: 150 W (maximum) when operating; less than 11 W in standby mode; 0 W in suspend mode and when CPU is in energy-saver mode

Environmental Requirements

- Temperature: 50 to 104 deg F (10 to 40 deg C)
- Humidity: 10% to 80%, noncondensing
- Altitude: 0 to 10,000 ft. (0 to 3,048 m)

Size and Weight

- Height: 16.8 in. (42.7 cm)
- Width: 16.2 in. (41.1 cm)
- Depth: 17.6 in. (45.2 cm)
- Weight: 49 lb. (23 kg)

Agency Approvals

- FCC Part 15 Class B
- CISPR 22 Class A (EN5008211)—complies with European EMC directive
- DOC Class B
- MPR II
- VCCI Class 2
- CE Mark
- EPA Energy Star compliant
- IEC 950

- UL1950
- CSA 950
- EN60950

System Requirements

- Power Macintosh, Macintosh Quadra, Macintosh Centris, Macintosh II (with video card), and PowerBook computers*
- System software version 7.1 or later

* Not all models and configurations are capable of driving the monitor to the highest resolution it supports.

Ordering Information

AppleVision 1710 Order No. M3322LL/A

- AppleVision 1710
- AppleVision software
- PC adapter
- Integrated, attached video and Apple Desktop Bus cable
- Power jumper cable
- Ambient light wand
- User's guide
- Limited warranty

Product specifications are subject to change. Check with your Apple reseller for the most current information about product specifications and configurations.

Support Information Services

Copyright 1996, Apple Computer, Inc.

Keywords: specsht

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 19293