

## **ProFile Hard Drive: Specifications (Discontinued)**

This article last reviewed: 10 May 1985

Model A9M0005 5 Megabyte (Discontinued) A9M0100 10 Megabyte (Discontinued)

- I. Technical Specifications
  - 1. Data Storage Characteristics:

	A9M0100	A9M0005
Data Capacity (formatted)		
in megabytes:	10	5
Data Surfaces:	4	4
Heads per Surface:	1	1
Track Spacing per inch:	345	254
Tracks per Surface:	306	152
Sectors per Track:	16	16
Sectors per Surface:	4896	2432
Block Size		
in bytes:	512	512
5.25" Floppy Equivalence:	70	35

2. Drive Characteristics:

Average Seek Time		
in milliseconds:	85	180
Data Transfer Rate		
in megabits/sec:	5	5
Rotational Start-up Time		
in seconds:	20	20
Drive Ready to Operate		
in seconds:	120	60
Rotational Speed		
in RPMs +/- 1%:	3600	3600
Mean Time Between Failure:		
in hours:	10,000	10,000

--Winchester technology

3. Interface:

a. Type: 8-bit parallel b. Connector: DB-25 c. Drives per Interface: 1 4. Power Requirements: a. U.S.: 110 VAC, 35 Watts b. Europe: 230 VAC c. Drive power source internal to the ProFile. 5. Environmental Requirements a. Temperature --Operating: 50 to 104 degrees F (10 to 40 degrees C) --Storage: -7.6 to 176 degrees F (-22 to 80 degrees C) b. Humidity --Operating: 20 to 80% noncondensing. --Storage: 1 to 95% 6. Physical Characteristics inches centimeters Height: 4.39 11.15 Width: 17.28 43.89 22.38 Depth: 8.81

pounds kilograms Weight: 11 5

II. Package

With the 5 Megabyte or 10 Megabyte ProFile package:

- 1. Apple ProFile hard-disk drive
- 2. Apple ProFile Accessory Kit including:
  - a. ProFile interface cable
  - b. System-specific ProFile owner's manual
  - c. Warranty and product registration
  - d. User Input Report
- 3. Included in the Apple II Accessory Kit:
  - a. Catalyst II software
  - b. Apple II SOS Driver and Utilities software
  - c. Backup II software
  - d. Apple II ProFile Interface Card
- 4. Included in the Apple III Accessory Kit:
  - a. Catalyst 2.0 software
  - b. Pascal ProFile Manager software
  - c. Backup III software
  - d. Apple III ProFile Interface Card
- III. System Configuration

--Either ProFile may be used the following Apple personal computers:

- 1. IIe
  - a. RAM: Minimum of 64 kilobytes
  - b. Operating System: ProDOS Pascal 1.2
  - c. Interface Cards:
    - -- The difference bewteen the 5Mb and 10Mb ProFile Interface cards is the ROM at location C6. The ROM is 341-027 for the 5Mb Card and 341-0299-B for the 10 Mb.
- 2. Apple III
- 3. Macintosh XL

NOTE: The Macintosh XL containing a built-in 10-megabyte hard disk requires a Parallel Interface Card (Order A6BB101, obsolete).

Features

Controller automatically scans for error conditions, relocating marginal data blocks elsewhere on the hard disk, if necessary. Copyright 1988 Apple Computer, Inc.

Keywords: SPECSHT

\_\_\_\_\_

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 1128