

Apple Hard Drives: Termination Requirements (10/94)

Article Created: 28 October 1994

TOPIC -----

Hard drives or DAT drives may need to have the termination resistors removed or made inoperative on certain configurations of multiple drive systems or WorkGroup Servers. Below is a brief description of termination requirements for the different systems or WorkGroup Servers.

DISCUSSION -----

Computer Model	Termination Requirement
Quadra/Centris 660 AV Quadra/Centris 610 Power Macintosh 6100/60 Workgroup Server 60 Workgroup Server 6150	Hard Drive needs termination
Macintosh IIvx, IIvi Quadra/Centris 650 Power Macintosh 7100/66	Hard Drive needs termination
Quadra 800/840 AV	Last drive in line needs termination. Remove termination from all other drives installed, including DAT.
Power Macintosh 8100/80 Workgroup Server 8150	 Has two internal cables: 1) Internal/external cable requires that all drives have no termination. Remove termination from all internal drives (termination is on cable) 2) The internal channel cable (max 1 drive only) requires termination.
Quadra 900 Quadra 950 Workgroup Server 95 Workgroup Server 9150	Remove termination from all internal drives (termination is on cable).

Copyright 1994, Apple Computer, Inc.

Keywords: hts

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 16628