



Tech Info Library

LaserWriter IINT: Specifications (Discontinued 10/91)

Article Created: 15 March 1991

Marking Engine

Canon LBP-SX laser xerographic

Processor

Motorola 68000 (12 MHz clock speed)

Memory

1MB ROM; 2MB RAM

Interfaces

AppleTalk, Apple Desktop Bus (for future expansion), and RS-232-C ports

Print Quality

All text and graphics printed at 300 by 300 dots per inch, full-page

Built-in Font Families

Times, Helvetica, Courier, Symbol, ITC Avant Garde Gothic, ITC Bookman, New Century Schoolbook, New Helvetica Narrow, Palatino, ITC Zapf Chancery, and ITC Zapf Dingbats

Speed

8 pages per minute maximum throughput (actual speed depends on images printed)

Printing Protocols

PostScript and a subset of the Diablo 630 command set

Print Materials

Letter, legal, A4, and B5 sizes using 16- to 20-lb. single-sheet photocopy bond, 8- to 34-lb. letterhead and colored stock, or transparency

overhead film. Envelopes, labels, and paper (up to 36-lb.) supported via manual feed. Envelopes also supported via optional envelope tray.

Print Capacities

- A paper cassette holds 200 sheets of 20-lb. paper.
- Envelope cassette holds 15 envelopes.

Printable Surface

- letter size: 8.0 by 10.5 in.
- legal: 8.0 by 13.0 in.
- A4: 7.41 by 10.86 in.
- B5: 7.69 by 10.16 in.

(Actual printable area may vary depending on application.)

Size and Weight

- Height: 8.6 in. (21.8 cm)
- Width: 20 in. (50.8 cm)
- Width: with letter tray attached, 26.4 in. (67.1 cm)
- Depth: 18.5 in. (47 cm)
- Weight: 45 lb. (20.25 kg)

Operating Environment

- Temperature: 50 to 90 degrees F (10 to 32 C)
- Humidity: 20% to 80%

Power Requirements

90 to 126 VAC, 50 to 60 Hz

Copyright 1991, Apple Computer, Inc.

Keywords: SPECSHT

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 6969