



Tech Info Library

LaserWriter Pro 810: Selecting Different Paper Trays (2/95)

Article Created: 4 May 1994

Article Reviewed/Updated: 8 February 1995

TOPIC -----

I am trying to get a LaserWriter PRO 810 to use the tabloid tray for plotting CADD files. I am using postscript, and have a copy of the LWPRO81_.ppd file. The problem I am having is trying to find the proper syntax. For most printers we use a command like:

```
statusdict begin n setdefaultpapertray end
```

where n is the tray number.

Several attempts at variations of this command, and using the .ppd to make more educated guesses have failed to get the desired results. I would appreciate any advice on the proper syntax to include in our postscript file.

DISCUSSION -----

Caution:

=====

If you choose to use the PostScript code provided in this article, you assume all risks involved in making these changes. PostScript code, if not entered correctly, can place the LaserWriter into a condition requiring service.

We also verified that the "setdefaultpapertray" command was not accepted by the LaserWriter Pro 810. Typically, most PostScript level 2 printers have compatibility operators for PostScript level 1 code so we are unsure why "setdefaultpapertray" is not working. However, there are other ways to choose paper trays:

1) The "setpapertray" compatibility operator can be used for the LaserWriter Pro 810 with the following values below:

- 0 for the Upper tray
- 1 for the Middle tray
- 2 for the Lower tray
- 4 for the Manual tray

Thus, "statusdict begin 1 setpapertray end" will use the Middle tray for

printing.

NOTE: Since this command does not exit the PS server loop, the paper tray selection is valid ONLY for the current job being printed.

By the way, this command does not work if the PostScript file being downloaded was generated by LaserWriter 8.x driver. This is because the paper selection code in LaserWriter 8.x driver overrides any code sent beforehand.

- 2) The following segments of code (taken from the LaserWriter Pro 810 PPD) will also select the various paper trays:

```
% Upper tray
currentpagedevice /InputAttributes get
0 get dup
null eq {pop}
{ dup
  /InputAttributes
  1 dict dup /Priority [0 1 2 3] put
  put setpagedevice
} ifelse
```

```
%Middle tray
currentpagedevice /InputAttributes get
1 get dup
null eq {pop}
{ dup
  /InputAttributes
  1 dict dup /Priority [1 0 2 3] put
  put setpagedevice
} ifelse
```

```
%Lower tray
currentpagedevice /InputAttributes get
2 get dup
null eq {pop}
{ dup
  /InputAttributes
  1 dict dup /Priority [2 0 1 3] put
  put setpagedevice
} ifelse
```

```
%Manual feed
<</ManualFeed true>> setpagedevice
```

Article Change History:

08 Feb 1995 - Added PostScript caution.
13 Oct 1994 - Corrected titled.

Support Information Services
Copyright 1994-95, Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 15269